

Description: 7.35W Linear LED Module / 287x8mm / 35LEDs / S7 P5


This LED Module Should be Operated On:

Any LED Driver designed to Provide output Current of 350mA and Voltage 21Vdc


ELECTRICAL DATA

NOMINAL INPUT VOLTAGE (V _{DC})	21
NOMINAL INPUT CURRENT (mA)	350
NOMINAL POWER CONSUMPTION(W)	7.35
PCB SIZE (mm)	LINEAR 287 x 8MM
PCB MATERIAL TYPE	FR-4
CCT	6500K / 4000K / 2700K
CALCULATED USABLE ARRAY FLUX (lm)	750 / 750 / 610
RECOMMENDED ATTACHMENT METHOD	Heatsink Compound
WEIGHT (gm)	8
MAXIMUM STORAGE TEMPERATURE (°C)	-40 to 100
MAXIMUM OPERATING AMBIENT TEMPERATURE (°C)	-35 to 50
MAXIMUM T _c (°C)	85
BEAM ANGLE	120°
CRI (Typ)	80

MECHANICAL DATA



WIRING DIAGRAMS



Driver must be grounded (if applicable).

Fulham extends a limited warranty only to the original purchaser or to the first user for a period of 3 years from the date of manufacture when properly installed and operated under normal conditions of use. For complete terms and conditions, please reference the Fulham product catalog (www.fulham.com)
Due to a program of continuous improvement, Fulham reserves the right to make modifications or variations in design or construction to the equipment described. © Fulham Company Limited, All Rights Reserved.