

T1240024V-30EE SPECIFICATIONS



- CV indoor Lights

SLIM Constant Voltage LED Driver

Flicker free, O/P Ripple Current < 10%

Output Wattage: 30W Max

Output Current: 1.25AOutput voltage 24Vdc

Application

General Specifications			
Rated Input Voltage	240VAC ±10%, 50/60Hz		
Operating Input Voltage Range	196-264VAC, 50/60Hz		
Input Current	0.20 A Max.		
Input Power	36W Max.		
Power Factor	>0.95 @ 230Vac Full Load		
THD	< 10% @ 230Vac Full Load		
Efficiency	>88%		
Driver Type	Constant Voltage		
Output Current	1.25A		
Output Voltage Range	24VDC <u>+</u> 5%		
Output Power	30W		
Number of Output Channels	1 Channel		
Dimming Controller Type/Dimming Range	NA		
RFI/EMI	CE		
Output Type	Class II		
Ambient Operating Temperature Range	-20°C to 45°C		
Max. Case Temperature	75°C		
Sound Rating	NA		
Input Surge Protection	Line-Neutral 1kV		
Protections	Input Over Current : NON-Resettable		
	Input Over Voltage : NA		
	Input Under Voltage : NA		
	Output Short Circuit : Auto recovery		
	Output Open Circuit : Auto recovery		
	Output Overload : YES		
	Over Temperature : YES		
Service Life	50,000 hours @ Tc 75°C		
Approvals / Class	Dry Locations		
Warranty	3 Years		
Weight	0.220Kg		




T1240024V-30EE


SPECIFICATIONS




THD vs. Load




Efficiency vs. Load




Power Factor Characteristics



Lifetime vs. Temperature Curve



Operating window



Fulham extends a limited warranty only to the original purchaser or to the first user for a period of <u>3 years @ Tc 75°C</u> from the date of manufacture when properly installed and operated under normal conditions of use. For complete terms and conditions, please reference the Fulham Product Catalog (www.fulham.com). Due to a program of continuous improvement, Fulham reserves the right to make modifications or variations in design or construction to the equipment described. © Fulham Company Limited, All Rights Reserved.




T1240024V-30EE

SPECIFICATIONS




Mechanical Data



Note: All Dimensions are in mm.

Tolerance=±0.5mm

Packaging



Master carton

OUTER DIMENSION				
L	W		Н	
445000	375n	Ш	150mm	
Net Weight	Gross Weight	Q	QUANTITY	
10.3 kg	11.0 kg		28 pc.	

Fulham extends a limited warranty only to the original purchaser or to the first user for a period of <u>3 years @ Tc 75°C</u> from the date of manufacture when properly installed and operated under normal conditions of use. For complete terms and conditions, please reference the Fulham Product Catalog (www.fulham.com). Due to a program of continuous improvement, Fulham reserves the right to make modifications or variations in design or construction to the equipment described. © Fulham Company Limited, All Rights Reserved.