

T1M1240012V-150PB.

SPECIFICATIONS

IP 67 SELV Equivalent



- · Constant Voltage LED Driver
- Output Wattage: 150W
- Output Current: 12.5A
- Output Voltage Range of 12Vdc
- · Aluminum extrusion enclousure and cables
- Suitable For Dry, Damp and Wet Locations
- Analog Dimming 1-10Vdc (10-100%)
- Ripple Current <5%(LF<200Hz) (pk/avg)
- 440Vac application @ 8Hrs
- OVP Cut-off
- Surge Immunity 4KV

General Specifications

Rated Input Voltage	220-240/240/230Vac,50/60Hz		
Operating Input Voltage Range	120-300Vac,50/60Hz		
Input Current	0.83A @ Rated I/P Voltage		
Input Power	172W @Rated I/P Voltage		
Power Factor	>0.95 @ Rated I/P Voltage & Max Load)		
THD	<10% @ Rated I/P Voltage & Max Load)		
Efficiency	>85% @ Rated I/P Voltage & Max Load)		
Driver Type	Constant Voltage		
Output Current	12.5A Max		
Output Voltage Range	12Vdc ±5%		
Output Power	150W		
Number of Output Channels	1 Channel		
Dimming Controller Type/Dimming Range	Analog 1 - 10Vdc (10-100%)		
Output Type	Class I		
Ambient Operating Temperature Range	-10°C to 55°C		
Max. Case Temperature	75°C		
Input Surge Protection	L-N-4KV, L-N-E-4KV As per EN 61000-4-5		
Protections	Input Over Current : Non Resettable (Fuse)		
	Input Over Voltage : Shutdown @ >325Vac, Auto recovery		
	440Vac for 8 hours		
	Input Under Voltage : NA		
	Output Short Circuit : Auto Recovery (HICCUP Mode) Continuous		
	Output Open Circuit : YES		
	Output to Ground short: YES		
	Output Overload : YES		
	Over Temperature : NA		
Service Life	50,000 Hours @ Tc Max		
Approvals / Class	SELV Equivalent ; Dry, Damp and Wet Locations		
Warranty	05 Years		
Weight	1.100 Kg		



T1M1240012V-150PB.

SPECIFICATIONS

IP 67 SELV Equivalent



Figure 1




Figure 3




Figure 5




Figure 7




Figure 2




Figure 4





Figure 6



Fulham extends a limited warranty only to the original purchaser or to the first user for a period of <u>05 years @ Tc max</u> from the date of manufacture when properly installed and operated under normal conditions of use. For complete terms and conditions, please reference the Fulham Product Catalog (www.fulham.com). Due to a program of continuous improvement, Fulham reserves the right to make modifications or variations in design or construction to the equipment described. © Fulham Company Limited, All Rights Reserved.




T1M1240012V-150PB.

SPECIFICATIONS










Product image



Note: All Dimensions are in mm.


Tolerance = ± 0.5mm

Wiring Diagrams



INPUT SIDE	LENGTH	LENGTH OUTPUT SIDE		
BLACK (L)		RED (+)	2 CORE CABLE 200mm	
WHITE (N)	3 CORE CABLE 200mm	BLACK (-)		
GREEN (E)	20011111	PURPLE (DIM +)	2 CORE CABLE	
•		GRAY (DIM -)	200mm	

Packaging




Master carton

OUTER DIMENSION						
L	L V		٧	Н		
235mm	nm 230)mm	155mm		
Net Weight		ross eight	Ql	UANTITY		
9.45kg	ę	9.9kg		09		

Installation Instructions:

- The driver should be installed in a dry, acid-free, oil free, fat-free environment.
- Do not exceed the declared Hot spot temperature(Tc max) under any circumstances.
- ≥ 08 cm clearance must be kept between the drivers as per installation diagram, When multiple drivers used.



Fulham extends a limited warranty only to the original purchaser or to the first user for a period of <u>05 years @ Tc max</u> from the date of manufacture when properly installed and operated under normal conditions of use. For complete terms and conditions, please reference the Fulham Product Catalog (www.fulham.com). Due to a program of continuous improvement, Fulham reserves the right to make modifications or variations in design or construction to the equipment described. © Fulham Company Limited, All Rights Reserved.